

VACUUM FORMED DISPLAY AND METHOD OF MAKING THE SAME

Description

1. Technical Field

The present disclosure is directed to a display having horizontal shelves, and more particularly, to an improved vacuum formed display having horizontal shelves with at least one partition to define separate compartments within the shelf.

2. Background of Related Art

Vacuum forming as a method of molding a display is well known in the art. In order to vacuum form the display a mold is utilized with a heat-softened sheet of plastic. Typically, the mold is porous or includes holes in a forming surface, and a vacuum is applied which evacuates air from between the surface and the heat-softened plastic sheet to bring the sheet into conformance with the surface. In this manner the sheet takes the shape of the surface of the mold. The completed product is then removed from the mold.

Vacuum formed displays are generally integrally molded to include a top, side and bottom walls, with shelves extending horizontally there across. Vacuum forming is a reliable and cost effective method to create such types of displays. However, it is sometimes desirable to have additional elements formed in the display, for example, shelves having a front lip, and/or partitions extending from the front to the back of the shelf to define separate compartments within the shelf to house items. In the past, it has not been possible to vacuum form a display including shelves with features such as front lips and/or partitions, because the lips and partitions on the shelves make it impossible to remove the vacuum formed display from the mold due to the undercuts defined by the front lip and/or front to rear partitions. In some cases, where shelves having these features are required, the shelves are molded separately and then attached in some mechanical way to the display, which itself is integrally molded without any shelves. This

1 results in a product which is more labor intensive, causing an increase in product cost, and also
2 makes it more likely that difficulties will result when assembling the shelves.

3 Other methods of forming displays also exist, other than vacuum forming. For example,
4 it is well known to form displays from cardboard blanks that are folded and manipulated which
5 results in the display having a plurality of shelves. One such display is illustrated in U.S. Patent
6 No. 5,678,492 to Pinkstone et al. which discloses a display box with shelving formed from a
7 single panel. In the '492 patent, a multi-tier display rack is formed from a flat, blank of sheet
8 material including four panels which create a front, rear and opposed side walls of the display
9 rack in the assembled position. In one embodiment, one panel includes sections which are
10 partially punched out to form shelves of the display rack when assembled. Each shelf includes a
11 slot therethrough. Another panel includes locking tabs which are partially punched out and
12 pushed through the slots to lock the shelves in place. While generally effective, displays of this
13 type lack the advantages of vacuum forming, namely, the ease of manufacture to produce
14 multiple displays in a cost effective manner.

15 While a variety of methods for making displays including shelves exist today, there is
16 continued need in the art for producing displays having shelves with partitions and/or lips, in a
17 readily reproducible and cost effective manner.

18 19 Summary

20 It is therefore an object of the vacuum formed display disclosed herein to provide a
21 display and method of making the same which is readily reproducible, cost effective, and which
22 can be utilized to produce a display having shelves including partitions to create one or more
23 multiple compartments, as well as other details such as a front lip, or the like.

24 The vacuum formed display includes a body portion, and one or more shelves integrally
25 formed with the body portion during vacuum forming. The shelves may have one or more
26 partitions, and include other details such as a raised lip along the front portion of the shelf, as
27 desired. To achieve a display having this configuration, when the display is vacuum formed, the
28 shelves are initially in a flat position, and lie generally in the same plane as a back wall of the
29 display. In this manner, the display (including the shelves) can be readily removed from the

1 mold. Once the mold is removed, the perimeter of the shelves, with the exception of a living
2 hinge portion which connects the shelf to the display, are die cut to separate the body of the
3 shelves from the back wall of the display. The shelves are then pivoted to a horizontal position
4 where they are supported between opposing side walls of the display. In one embodiment,
5 integrally molded support ledges which extend inwardly from the side walls of the interior of the
6 display provide a support for holding the shelves in their desired horizontal position. The
7 structure of the support ledges provides the shelves with sufficient support so that products may
8 be placed on the shelves during use. In another embodiment, cooperating detents may be
9 provided on the inner surface of the side walls of the display, and above the support ledges, in
10 order to hold the shelves more securely in the horizontal display position. As will be
11 appreciated, when the shelves are die cut and pivoted to their horizontal position, a
12 corresponding opening remains on the back wall of the display. This opening may be covered by
13 securing a printed card or sticker to the back of the display. The card may include any desired
14 product information, advertising message or other indicia. Alternately, the opening may remain
15 and the display may be mounted to a suitable backing.

17 **Brief Description of the Drawings**

18 It should be understood that the drawings are provided for the purpose of illustration only
19 and are not intended to define the limits of the invention. The foregoing and other objects and
20 advantages of the embodiments described herein will become apparent with reference to the
21 following detailed description when taken in conjunction with the accompanying drawings in
22 which:

23 Fig. 1 is a front perspective view of a vacuum formed display as disclosed herein prior to
24 assembly;

25 Fig. 2 is a front elevational view of the embodiment of Fig. 1;

26 Fig. 3 is a cross sectional view taken along lines 3-3 of Fig. 2;

27 Fig. 4 is an enlarged cross sectional view of the top portion of Fig. 3;

28 Fig. 5 is a cross sectional view taken along lines 5-5 of Fig. 4;

1 Fig. 6 is a front perspective view of the embodiment of Fig. 1 illustrating movement of
2 the shelf into the engaged or display position;

3 Fig. 7 is a front elevational view of Fig. 6;

4 Fig. 8 is a cross sectional view taken along lines 8-8 of Fig. 7;

5 Fig. 9 is a side cross sectional view showing the shelf moving from the upward or non-
6 assembled position to the lowered or assembled position;

7 Fig. 10 is a cross sectional view taken along lines 10-10 of Fig. 8(?);

8 Fig. 11 is a front perspective view of the vacuum formed display of Fig. 1 in the showing
9 the shelf in the fully engaged display position;

10 Fig. 12 is a front perspective view of Fig. 11; and

11 Fig. 13 is a cross sectional view taken along lines 13-13 of Fig. 12.

12 13 Detailed Description of the Illustrative Embodiments

14 A vacuum formed display 10 includes a body portion 12 having a top wall 14, a bottom
15 wall 16, opposing side walls 17, 18, back wall 20, and one or more shelves 22, as shown in Figs.
16 1-13. In the present embodiment, a single shelf 22 is illustrated which includes a pair of
17 compartments 24a, 24b for holding and displaying articles, although any number of shelves
18 and/or compartments may be formed in the display as would be known to one of skill in the art.
19 The shelf 22 is formed as a unitary piece with the body portion 12, such that perimeter 23 of the
20 shelf lies generally in the same plane as the back wall 20 of the display. Likewise, the back 26a,
21 26b of the compartments lie in a plane generally parallel to the plane of the back wall 20.
22 Because the shelves and any compartments are parallel to the plane of the back wall, once the
23 display is molded it can be readily removed from the mold without difficulty, as described in
24 greater detail below. In the present embodiment, a pair of support ledges 28a, 28b may also be
25 molded as unitary members of the body portion 12. The support ledges 28a, 28b are preferably
26 molded on an inner surface 29a, 29b of opposing side walls 16, 18, and are positioned along the
27 inner surface in order to provide support to the shelf 22 when it is rotated into the assembled
28 position. A pair of cooperative detents 30a, 30b may also be provided on the inner surface of the

1 opposing side walls **16, 18**, spaced just above each of the ledges. The detents lend additional
2 support to the shelf when it is pivoted into the assembled position, as discussed below.

3 Referring now to Figs. 2-10, in order to assemble the display and move the shelf **22** from
4 the non-assembled, molding position (Fig. 2) to the assembled, display position (Fig. 6), the
5 perimeter **23** of the shelf is separated from the back wall **20** of the display. In the present
6 embodiment, the perimeter of the shelf is die cut with the exception of a living hinge **32** (Fig. 8),
7 which remains connected to the back wall **20** in order to provide the connection between the
8 shelf **22** and the display. As best shown in Fig. 6, the perimeter **23** of the shelf **22** may be cut
9 such that a pair of tabs **34a, 34b** are formed which extend from the shelves, toward the inner
10 surface **29a, 29b** of the opposing side walls **17, 18**, respectively. The tabs **34a, 34b** may be
11 provided to give additional support to the shelf once assembled. The tabs are preferably sized so
12 that they are supported on corresponding ledges **28a, 28b**, and under detents **30a, 30b** in order to
13 lock shelf **22** in place, in the present embodiment (Fig. 8). The front portion, or forward lip **36** of
14 the perimeter **23** may preferably be cut inward from the tabs, so that a sufficient clearance is
15 formed between the inner surface of the side walls and the front portion of the shelf in order to
16 aid in rotating the shelf into the assembled position.

17 Once the shelf **22** has been die cut from the display and moved into the assembled
18 position, a corresponding opening **38** remains in the back of the display. In order to provide a
19 more finished look to the display, the opening **38** may be covered by securing a sticker or card **40**
20 (Fig. 11) over the opening. The card **40** may include any desired information, or indicia, such as
21 product information or advertising, as desired. Alternately, the opening may remain and the
22 display may be mounted to a suitable backing.

23 The display **10**, and one or more shelves **22** may be any of a number of shapes and have a
24 variety of sizes, as would be known to those of skill in the art. In the present embodiment, the
25 display has a rectangular shape with the length, "l", of the display from the outer edge of the top
26 wall to the outer edge of the bottom wall being about 19.5 inches, and the width, "w", from the
27 outer edge of one side wall to the outer edge of the other side wall being about 15 inches. The
28 shelf **22** may also have a variety of shapes and sizes, depending upon the shape and dimensions
29 of the body of the display. In the present embodiment, the shelf **22** has a depth, "d", (Fig. 8) of

1 about 6.5 inches , and has a width (“w_b”) of about 11.75 inches at the back, including tabs **34a**,
2 **34b**, and a width (“w_f”) of about 11 inches at the front lip. The shelf may include one or more
3 compartments. In the present embodiment, the shelf **22** includes a partition or raised wall **42**
4 which divides the shelf into two compartments **24a**, **24b**. In the present embodiment, partition
5 **42** extends from the front portion **36** to the rear portion **44** of the shelf. Each of the two
6 compartments **24a**, **24b** have a bottom or base **26a**, **26b** to support a product thereon. The base
7 of each compartment may further include a raised wall, or lip, extending along the perimeter of
8 the base. As will be appreciated, the size and shapes of the compartments may readily be varied,
9 as would be known to those of skill in the art. In addition, although the present embodiment
10 illustrates the compartments **24a**, **24b** being bounded on all sides by a raised wall **43**, the shelf
11 may alternately include only a raised front lip in order to prevent product from sliding off the
12 shelf. In such a case the shelf may include a single large compartment, if desired.

13 A method of making a vacuum formed display including at least one shelf having a raised
14 wall to define separate compartments, or a lip, will now be described with reference to the
15 drawings.

16 As shown in Figs. 1-5 the display **10** is initially vacuum molded such that the body
17 portion **12** and shelf **22** are a single, unitary display. In this unassembled position, the shelf **22**
18 lies in a vertical plane defined by the back wall **20** of the display, with the compartments **24a**,
19 **24b** laying substantially parallel to the vertical plane. The display is vacuum formed using
20 conventional techniques, as known to those of skill in the art. Once the vacuum forming is
21 complete, the mold can be readily removed, as conventional, because the shelf **22** and any
22 compartments and/or lips are positioned parallel to the plane of the back wall **20** of the display.
23 There are no undercuts present in the unassembled position to prevent the display from being
24 removed from the mold. Once the display is removed from the mold the shelf **22** is cut around
25 its perimeter **23** so that it can be separated from the back wall **20** of the display and moved into
26 the assembled position (Fig. 6). When the shelf is cut, it is preferably cut along three sides only,
27 so that it remains connected to the back wall along one side by a living hinge **32**. In the
28 illustrated embodiment, the shelf is cut along opposing sides and a top edge so that it remains
29 connected at a bottom edge. Alternately, the shelf could be cut along the bottom and side edges

1 and remain connected at the top edge. In either case, once the shelf has been cut it is pivoted
2 (downward in the present embodiment) into the horizontal position, where the shelf lies in a
3 plane substantially perpendicular to the plane of the back wall. The display may be molded with
4 a pair of optional support ledges **28a**, **28b** on the inner surface of opposing side walls **16**, **18**, in
5 order to provide support to the shelf **22** when it is rotated into the assembled position. A pair of
6 cooperative detents **30a**, **30b** may also be provided on the inner surface of the opposing side
7 walls **16**, **18**, spaced just above each of the ledges. The detents lend additional support to the
8 shelf and aid in locking the shelf in place when it is pivoted into the assembled position, as
9 discussed below. If ledges **28a**, **28b** are provided, it is desirable to cut the shelf along the
10 perimeter so that a pair of tabs **34a**, **34b** are formed which extend from the shelf, toward the
11 inner surface of the opposing side walls **16**, **18**. The tabs are sized so that they are supported on
12 corresponding ledges **28a**, **28b**, and under detents **30a**, **30b** in order to lock shelf **22** in place, in
13 the present embodiment (Fig. 8). Once the shelf is cut, pivoted and locked in place, a
14 corresponding opening **38** remains in the back of the display. In order to provide a more finished
15 look to the display, the opening **38** may be covered by securing a sticker or card **40** (Fig. 9) over
16 the opening. The card **40** may include any desired information, or indicia, such as product
17 information or advertising, as desired.

18 The display and method of making the same disclosed herein is readily reproducible, cost
19 effective, and can be utilized to produce a display having shelves including one or more multiple
20 compartments, as well as other details such as a front lip, or the like.

21 It will be understood that various modifications may be made to the embodiments
22 disclosed herein. For example, the shape and size of the display, shelves and compartments may
23 be readily varied, as would be known to those of skill in the art. In addition, the number of
24 compartments and shelves may be varied. Also, the shelves may be pivoted upward, instead of
25 downward, as would be known to those of skill in the art. Therefore, the above description
26 should not be construed as limiting, but merely as exemplifications of preferred embodiments.
27 Those skilled in the art will envision other modifications within the scope, spirit and intent of the
28 invention.

29 WHAT IS CLAIMED IS: